

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier

Trade name: C.A.R.FIT MULTI PUTTY

1.2. Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available

Application of the substance / the mixture Knife filler/ Surfacers

1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier:

August Handel GmbH
Seestrasse 33 - Brandenburg Park
DE 14974 Ludwigsfelde (Berlin)
info@augusthandel.com

• Further information obtainable from:

Phone: +49 (0) 3378.203330 info@augusthandel.com

1.4. Emergency telephone number:

Phone: +49 (0)3378.2033355

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R20-48/20-63: Harmful by inhalation. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child.



Xi; Irritant

R36/38: Irritating to eyes and skin.

R10: Flammable.

- Information concerning particular hazards for human and environment:**

The product has to be labeled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS08

Signal word Danger

Hazard-determining components of labelling:

Styrene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition / information on ingredients

3.2. Chemical characterization: Mixtures

Description:

Mixture of substance listed below with nonhazardous additions.

Dangerous components:

CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	styrene ☒ Xn R20-48/20-63; ☒ Xi R36/38 R10	≤20%
	☒ Flam. Liq. 3, H226; ☒ Repr. 2, H361d; STOT RE 1, H372; ☒ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. ☒ Xn R65; ☒ Xi R37; ☒ N R51/53 R10-66-67	≤1.0%
	☒ Flam. Liq. 3, H226; ☒ Asp. Tox. 1, H304; ☒ Aquatic Chronic 2, H411; ☒ STOT SE 3, H335-H336	

- Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- After skin contact:** Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing:** If symptoms persist consult doctor.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing agents:** CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents:** Water with full jet

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

- Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2. Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

6.3. Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
6.4. Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

- Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

7.2. Conditions for safe storage, including any incompatibilities

- Storage:**
- Requirements to be met by storerooms and receptacles:**

No special requirements.

- Information about storage in one common storage facility:** Store away from foodstuffs.
- Further information about storage conditions:** Keep container tightly sealed.

Storage class: 3

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities:** No further data; see item 7.

8.1. Control parameters

Ingredients with limit values that require monitoring at the workplace:

100-42-5 Styrene

WEL

Short-term value: 1080 mg/m³, 250 ppm

Long-term value: 430 mg/m³, 100 ppm

- Additional information:** The lists valid during the making were used as basis.

8.2. Exposure controls

- Personal protective equipment:**
- General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation / the chemical mixture.



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

General Information

- | | |
|---|---|
| • Appearance | |
| Form: | Fluid |
| Color: | According to product specification |
| Odour: | Characteristic |
| • Odour threshold: | Not determined |
| • pH: | Not determined |
| • Melting point / Melting range: | Undetermined |
| • Boiling point / Boiling range: | 145 °C |
| • Flash point: | 34 °C (DIN 53213) |
| • Flammability (solid, gaseous): | Not applicable. |
| • Ignition temperature: | 480 °C (DIN 51794) |
| • Decomposition temperature: | Not determined |
| • Self-igniting: | Product is not selfigniting |
| • Danger of explosion: | Product is not explosive. However, formation of explosive air / vapour mixtures are possible. |
| • Explosion limits: | |
| Lower: | 1.2 Vol % |
| Upper: | 8.9 Vol % |
| • Vapour pressure at 20 °C: | 6 hPa |
| • Density at 20 °C: | 1.83 g/cm ³ (DIN 53217) |
| • Relative density | Not determined. |
| • Vapour density | Not determined. |
| • Evaporation rate | Not determined. |
| • Solubility in / Miscibility with water: | Not miscible or difficult to mix |
| • Partition coefficient (n-octanol/water): | Not determined. |
| • Viscosity: | |
| Dynamic at 20 °C: | 10000 mPas |
| Kinematic: | Not determined |

- **Solvent content:**
VOC (EC): 0.31 %
Solids content (weight-%): 86.3 %

9.2. Other information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

- **Thermal decomposition / conditions to be avoided**

No decomposition if used according to specifications.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products:

Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

- **Acute toxicity**

LD/ LC50 values relevant for classification:

100-42-5styrene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rat)
Inhalative	LC50/ 4 h (Dämpfe)	11.8 mg/l (rat)

- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Repr. 2

SECTION 12: Ecological information

12.1. Toxicity

- **Aquatic toxicity:**

No further relevant information available.

12.2. Persistence and degradability

No further relevant information available.

12.3. Bioaccumulative potential

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

- Additional ecological information:**

- General notes:**

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

12.5. Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6. Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances
-----------	---

- Uncleaned packaging:**

- Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1. UN-Number**

- ADR, IMDG, IATA** UN3269

- 14.2. UN proper shipping name**

- ADR** 3269 POLYESTER RESIN KIT

- IMDG, IATA** POLYESTER RESIN KIT

- 14.3. Transport hazard class(es)**

- ADR**



- Class** 3 (F3) Flammable liquids

- Label** 3

- IMDG, IATA**



- Class** 3 Flammable liquids

- Label** 3

- 14.4. Packing group**

- ADR, IMDG, IATA** III

- 14.5. Environmental hazards:**

- Marine pollutant:** No

- 14.6. Special precautions for user** Warning: Flammable liquids

- Danger code (Kemler):** -

- EMS Number:** F-E, S-D

- **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable
- **Transport/Additional information:**
- **ADR**
- **Transport category** 3
- **Tunnel restriction code** E
- **IMDG**
- **Limited quantities (LQ)** 5L
- **UN "Model Regulation":** UN3269, POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- **National regulations:**

Class	Share in %
NK	10-<25

15.2. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

R10 Flammable.

R20 Harmful by inhalation.

R36/38 Irritating to eyes and skin.

R37 Irritating to respiratory system.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R63 Possible risk of harm to the unborn child.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Repr. 2: Reproductive toxicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

- * Data compared to the previous version altered.