(in accordance with Regulation (EU) 2020/878)

### **Acrylic food hardener - H1005**

Version 1 Date of compilation: 9/12/2021

Version 2 (replaces version 1) Revision date: 16/06/2023



Page 1 of 10 Print date: 16/06/2023

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: Acrylic Food Hardener

Product Code: H1005

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against.

Hardener for water based varnishes

### Uses advised against:

Uses other than those recommended.

### 1.3 Details of the supplier of the safety data sheet.

Company: STARDUSTCOLORS SAS

Address: ZA de Tesan, plan Sud

City: 30126 Saint-Laurent-Des-Arbres

Country: FRANCE Telephone:

Heilepnone: +33 4 66 50 61 66 info@stardustcolors.com www.stardustcolors.com

**1.4 Emergency telephone number:** +33 1 45 42 59 59 (Only available during office hours; Monday-Thursday; 08:00-13:30;

14:30-18:00 Friday; 08:00-14:00)

#### **SECTION 2: HAZARDS IDENTIFICATION.**

### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Acute Tox. 4: Harmful if inhaled.

Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

STOT SE 3: May cause respiratory irritation. Skin Sens. 1: May cause an allergic skin reaction.

#### 2.2 Label elements.

### Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



#### Signal Word:

### Warning

### Hazard statements:

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

P321 Specific treatment (see ... on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

(in accordance with Regulation (EU) 2020/878)

### **Acrylic food hardener - H1005**

Version 1 Date of compilation: 9/12/2021

Version 2 (replaces version 1) Revision date: 16/06/2023



Page 2 of 10 Print date: 16/06/2023

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container to ...

Contains: n-butyl acetate HDI Polyisocyanate

#### 2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.**

### 3.1 Substances.

Not Applicable.

#### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 160994-68-3	HDI Polyisocyanate	55 - 100 %	Acute Tox. 4, H332 - Aquatic Chronic 3, H412 - STOT SE 3, H335 - Skin Sens. 1, H317	-
Index No: 607-025- 00-1 CAS No: 123-86-4 EC No: 204-658-1 Registration No: 01- 2119485493-29-XXXX	[2] n-butyl acetate	1 - 20 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-

<sup>(\*)</sup> The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

### **SECTION 4: FIRST AID MEASURES.**

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance. The use of personal protective equipment is recommended for people providing first aid (see section 8).

#### Eye contact

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

### Skin contact.

<sup>[2]</sup> Substance with a national workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2020/878)

### **Acrylic food hardener - H1005**

Version 1 Date of compilation: 9/12/2021

Version 2 (replaces version 1) Revision date: 16/06/2023



Page 3 of 10
Revision date: 16/06/2023 Print date: 16/06/2023

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

### **SECTION 5: FIREFIGHTING MEASURES.**

The product does not present any particular risk in case of fire.

#### 5.1 Extinguishing media.

#### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### **Unsuitable extinguishing media:**

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

### 5.2 Special hazards arising from the substance or mixture.

#### Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

#### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

#### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

(in accordance with Regulation (EU) 2020/878)

### **Acrylic food hardener - H1005**

Version 1 Date of compilation: 9/12/2021

Version 2 (replaces version 1) Revision date: 16/06/2023

STARDUST

Page 4 of 10 Print date: 16/06/2023

For later elimination of waste, follow the recommendations under section 13.

### **SECTION 7: HANDLING AND STORAGE.**

#### 7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

#### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

#### 7.3 Specific end use(s).

Not available.

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.**

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³
		United	Eight hours	150	724
		Kingdom [1]	Short term	200	966
		Éiro [2]	Eight hours	150	710
		Éire [2] Short term 200	200	950	
n but d acctate	123-86-4	United States [3] (Cal/OSHA)	Eight hours	150	
n-butyl acetate			Short term	200	
		United States	Eight hours	150	
		[4] (NIOSH) Short term 200 United States Eight hours 150			
			Eight hours	150	710
		[5] (OSHA)	Short term		

<sup>[1]</sup> According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
	DNEL	Inhalation, Chronic, Systemic effects	480
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	(Workers)		(mg/m³)
	DNEL	Inhalation, Chronic, Systemic effects	102,34
	(Consumers)		(mg/m <sup>3</sup> )
	DNEL	Inhalation, Short term, Systemic effects	960
	(Workers)		(mg/m³)

<sup>[2]</sup> According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

<sup>[3]</sup> California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

<sup>[4]</sup> National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

<sup>[5]</sup> Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

(in accordance with Regulation (EU) 2020/878)

### **Acrylic food hardener - H1005**

Version 1 Date of compilation: 9/12/2021





Print date: 16/06/2023

Page 5 of 10

 DNE		050.7
DNEL	Inhalation, Short term, Systemic effects	859,7
(Consumers)		(mg/m³)
DNEL	Inhalation, Chronic, Local effects	480
(Workers)		(mg/m³)
DNEL	Inhalation, Chronic, Local effects	102,34
(Consumers)		(mg/m³)
DNEL	Inhalation, Short term, Local effects	960
(Workers)		(mg/m³)
DNEL	Inhalation, Short term, Local effects	859,7
(Consumers)		(mg/m³)
DNEL	Oral, Chronic, Systemic effects	3,4 (mg/kg
(Consumers)		bw/day)
DNEL	Dermal, Chronic, Systemic effects	3,4 (mg/kg
(Consumers)		bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
	aqua (freshwater)	0,18 (mg/l)
	aqua (marine water)	0,018 (mg/l)
n-butyl acetate CAS No: 123-86-4 EC No: 204-658-1	aqua (intermittent releases)	0,36 (mg/l)
	STP	35,6 (mg/l)
	sediment (freshwater)	0,981 (mg/kg
	, , ,	sediment dw)
	sediment (marine water)	0,0981
	, , , ,	(mg/kg
		sediment dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.**

#### 9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Not applicable/Not available due to the nature/properties of the product

Odour: CHARACTERISTIC

Odour threshold: Not applicable/Not available due to the nature/properties of the product Melting point: Not applicable/Not available due to the nature/properties of the product Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: 126 °C

Flammability: Not applicable/Not available due to the nature/properties of the product Lower explosion limit: Not applicable/Not available due to the nature/properties of the product Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: 69 °C

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: Not applicable/Not available due to the nature/properties of the product

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product Hydrosolubility: Not applicable/Not available due to the nature/properties of the product Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: 12,61

(in accordance with Regulation (EU) 2020/878)

### **Acrylic food hardener - H1005**

Version 1 Date of compilation: 9/12/2021

Version 2 (replaces version 1) Revision date: 16/06/2023

STARDUST COLORS

Page 6 of 10 Print date: 16/06/2023

Absolute density: Not applicable/Not available due to the nature/properties of the product

Relative density: 0,88

Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product

#### 9.2 Other information

Not applicable/Not available due to the nature/properties of the product

### **SECTION 10: STABILITY AND REACTIVITY.**

#### 10.1 Reactivity.

The product does not present hazards by their reactivity.

#### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

#### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

#### 10.4 Conditions to avoid.

Avoid any improper handling.

#### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

### 10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

### **SECTION 11: TOXICOLOGICAL INFORMATION.**

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008.

Toxicological information about the substances present in the composition.

Name		Acute toxicity				
	Name		Test	Kind	Value	
			LD50	Rat	10800 mg/kg bw [1]	
n-butyl acetate		Oral	[1] Acute Toxicity Data. Journal of the American College of Toxicology, Part B. Vol. 1, Pg. 196, 1992			
			LD50	Rabbit	>17600 mg/kg bw [1]	
		Dermal		aterial Data Har 1, Pg. 7, 1974	ndbook, Vol.1: Organic Solvents,	
			LC50	Rat	1.85 mg/l/4 h [1]	
CAS No: 123-86-4	EC No: 204-658-1	Inhalation	[1] Inhalati	ion Toxicology.	Vol. 9, Pg. 623, 1997	

a) acute toxicity;

Product classified:

Acute toxicity (Inhalation), Category 4: Harmful if inhaled.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Inhalation) = 11 mg/l/4 h (Fumes)

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Not conclusive data for classification.

(in accordance with Regulation (EU) 2020/878)

### **Acrylic food hardener - H1005**

Version 1 Date of compilation: 9/12/2021

Version 2 (replaces version 1) Revision date: 16/06/2023



Page 7 of 10 Print date: 16/06/2023

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3: May cause respiratory irritation.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

#### 11.2 Information on other hazards.

### **Endocrine disrupting properties**

This product does not contain components with endocrine-disrupting properties with effects on human health.

### Other information

There is no information available on other adverse health effects.

### **SECTION 12: ECOLOGICAL INFORMATION.**

### 12.1 Toxicity.

Name	Ecotoxicity			
Name	Туре	Test	Kind	Value
n-butyl acetate	Fish	LC50 Fish 81 mg/l (96 h) [1] [1] Wellens, H. 1982. Comparison of the Sensitivity of Brachydanio rerio and Leuciscus idus by Testing the Fish Toxicity of Chemicals and Wastewaters. Z.Wasser-Abwasser-Forsch. 51(2):49-52 (GER) (ENG ABS). Dawson, G.W., A.L. Jennings, D. Drozdowski, and E. Rider 1977. The Acute Toxicity of 47 Industrial Chemicals to Fresh and Saltwater Fishes. J.Hazard.Mater. 1(4):303-318 (OECDG Data File)		
	Aquatic invertebrates	EC50	Daphnia sp. tion, 1959	44 mg/l (48 h) [1]
	Aquatic plants	EC50	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	674.7 mg/l (72 h) [1]
CAS No: 123-86-4 EC No: 204-658-1		Umweltbur		h inhibition test, according to deral Environment Agency) ry 1984)

### 12.2 Persistence and degradability.

(in accordance with Regulation (EU) 2020/878)

### **Acrylic food hardener - H1005**

Version 1 Date of compilation: 9/12/2021

Version 2 (replaces version 1) Revision date: 16/06/2023



Page 8 of 10 ion date: 16/06/2023 Print date: 16/06/2023

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

#### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name		Bioaccumulation				
		Log Pow	BCF	NOECs	Level	
n-butyl acetate		1,78	_	_	Very low	
CAS No: 123-86-4	EC No: 204-658-1	1,76	-	-	very low	

### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### 12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

#### 12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

### **SECTION 13: DISPOSAL CONSIDERATIONS.**

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

### **SECTION 14: TRANSPORT INFORMATION.**

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

### 14.1 UN number or ID number.

Transportation is not dangerous.

### 14.2 UN proper shipping name.

Description:

ADR/RID: Not classified as hazardous for transport. IMDG: Not classified as hazardous for transport.

ICAO/IATA: Not classified as hazardous for transport.

### 14.3 Transport hazard class(es).

Transportation is not dangerous.

### 14.4 Packing group.

Transportation is not dangerous.

### 14.5 Environmental hazards.

Transportation is not dangerous.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): Not applicable.

(in accordance with Regulation (EU) 2020/878)

### **Acrylic food hardener - H1005**

Version 1 Date of compilation: 9/12/2021

Version 2 (replaces version 1) Revision date: 16/06/2023



Page 9 of 10 Print date: 16/06/2023

### 14.6 Special precautions for user.

Transportation is not dangerous.

#### 14.7 Maritime transport in bulk according to IMO instruments.

Transportation is not dangerous.

### **SECTION 15: REGULATORY INFORMATION.**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC) VOC content (p/p): 3,85 % VOC content: 33,88 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

#### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

### Classification codes:

Acute Tox. 4: Acute toxicity (Inhalation), Category 4

Aquatic Chronic 3: Chronic effect to the aquatic environment, Category 3

Flam. Liq. 3: Flammable liquid, Category 3

STOT SE 3: Specific target organ toxicity following a single exposure, Category 3

Skin Sens. 1 : Skin sensitiser, Category 1

### Changes regarding to the previous version:

- Modification of specific hazards (SECTION 2.3).
- Changes in the composition of the product (SECTION 3.2).
- Modification in the firefighting measures (SECTION 5.2).
- Modifications in the accidental release measures (SECTION 6.1).
- Modifications in the accidental release measures (SECTION 6.2).
- Modification of exposure data (SECTION 8.1).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Change in the hazard classification (SECTION 11.1).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- National legislative changes (SECTION 15.1).
- Elimination of abbreviations and acronyms (SECTION 16).

(in accordance with Regulation (EU) 2020/878)

### **Acrylic food hardener - H1005**

Version 1 Date of compilation: 9/12/2021 Version 2 (replaces version 1)

Revision date: 16/06/2023



Page 10 of 10 Print date: 16/06/2023

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

BCF: Bioconcentration factor.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

NOEC: No observed effect concentration.

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are

not expected in the environmental compartment.

### Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2020/878. Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.